

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
18 April 2002 (18.04.2002)

PCT

(10) International Publication Number
WO 02/30326 A2

- (51) International Patent Classification⁷: **A61F 2/02**
- (21) International Application Number: PCT/US01/31729
- (22) International Filing Date: 10 October 2001 (10.10.2001)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
09/686,251 11 October 2000 (11.10.2000) US
60/304,165 11 October 2000 (11.10.2000) US
- (71) Applicant: **HEARTSTENT CORPORATION** [US/US];
7145 Boone Ave. N. Suite 150, Brooklyn Park, MN 55428 (US).
- (72) Inventors: **VANNEY, Guy, P.**; 10927 Buchanan Street, Blaine, MN 55434 (US). **ENO, Robert, A.**; 2535 Medicine Ridge Road, Plymouth, MN 55441 (US). **GROTH, Dale, M.**; 3224 Colorado Avenue South, St. Louis Park, MN 55416 (US).
- (74) Agent: **BRUESS, Steven, C.**; Merchant & Gould P.C., P.O. Box 2903, Minneapolis, MN 55402-0903 (US).
- (81) Designated States (*national*): AE, AG, AL, AM, AT, AT (utility model), AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, CZ (utility model), DE, DE (utility model), DK, DK (utility model), DM, DZ, EC, EE, EE (utility model), ES, FI, FI (utility model), GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PH, PL, PT, RO, RU, SD, SE, SG, SI, SK, SK (utility model), SL, TJ, TM, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZW.
- (84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- Published:**
— *without international search report and to be republished upon receipt of that report*
- For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*



WO 02/30326 A2

(54) Title: **STABILIZED TRANSMYOCARDIAL IMPLANT**

(57) Abstract: A transmyocardial implant for establishing a blood flow path through a myocardium between a heart chamber and a lumen of a coronary vessel residing at an exterior of said wall includes a hollow conduit having a vessel portion and a myocardial portion. The vessel portion is sized to be received within the lumen. The said myocardial portion is sized to extend from the vessel through the myocardium and into the chamber. The conduit has an open first end and an open second end on respective ones of the vessel and myocardial portions to define a blood flow pathway within an interior of the conduit between the first and second end. At least the myocardial portion of the conduit is formed of a conduit material sufficiently rigid to resist deformation and closure of the pathway in response to contraction of the myocardium. The conduit material is resistant to thrombus formation. An anchor is secured to the conduit and positioned to overlie and be secured to an epicardial surface of the myocardium when the vessel portion of the conduit is secured within the lumen.

STABILIZED TRANSMYOCARDIAL IMPLANT

This application is being filed as a PCT application on 10 October 2001 by HEARTSTENT CORPORATION, a United States national and resident,
5 designating all countries except US. The application claims priority to US Application No. 09/686,251 filed 11 October 2000 and later converted to Provisional Application No. 60/304,165.

BACKGROUND OF THE INVENTION

10 1. Field of the Invention

This invention pertains to an implant for directing blood flow directly between a chamber of the heart and a coronary vasculature. More particularly, this invention pertains to such an implant with an enhanced design for securing placement of the implant.

15

2. Description of the Prior Art

Commonly assigned U.S. Pat. Nos. 5,755,682 and 5,944,019 teach an implant for defining a blood flow conduit directly from a chamber of the heart to a lumen of a coronary vessel. An embodiment disclosed in the aforementioned
20 application teaches an L-shaped implant in the form of a rigid conduit. The conduit has one leg sized to be received within a lumen of a coronary artery and a second leg sized to pass through the myocardium and extend into the left ventricle of the heart. As disclosed in the above-referenced patent application, the conduit is rigid and remains open for blood flow to pass through the conduit during both systole and
25 diastole. The conduit penetrates into the left ventricle in order to prevent tissue growth and occlusions over an opening of the conduit.

Commonly assigned U.S. Pat. No. 5,984,956 teaches an implant such as that shown in the aforementioned '682 and '019 patents with an enhanced fixation structure. One embodiment of the enhanced fixation structure includes a fabric cuff
30 surrounding the conduit to facilitate tissue growth on the exterior of the implant. The fabric is described as a polyester cuff having interstitial spaces into which tissue may grow.

Implants such as those shown in the aforementioned patents include a portion to be placed within a coronary vessel and a portion to be placed within the

myocardium. When placing a portion of the implant in the coronary artery or other coronary vessel, the artery is incised by an amount sufficient to insert the implant. Preferably, the artery is ligated distal to an obstruction. A transverse incision is made through the artery distal to the ligation. Tools and procedures for such an
5 implantation are shown and described in commonly assigned and copending U.S. Pat. No. 6,029,672.

In the foregoing references, a constantly open blood flow path is preferred. However, the references also teach a conduit with a valve which closes during diastole. The afore-mentioned U.S. Pat. No. 5,944,019 teaches a conduit with a
10 valve which only partially closes during diastole to permit a washing back-flow.

Conduits which include a valve or which otherwise close during the heart cycle are shown in U.S. Pat. No. 5,287,861; U.S. Pat. No. 5,409,019 and 5,429,144 (all to Wilk) and PCT International Publication Nos. WO 98/08456 and WO
98/46115. The alleged benefits of a valve in such a conduit are described in Kashem
15 et al., "Feasibility Study of Left Ventricle to Coronary Artery Perfusion for Severe Coronary Artery Diseases", ASAIO Journal, Vol. 45, No. 2 (March-April, 1999) (Abstract).

After an implant with a fabric cuff is placed in the myocardium, the tissue of the myocardium grows into the cuff. A healing process takes place over time and
20 includes fibrosis at the cuff. Such healing may include contraction of tissue around the implant. Such healing can cause the implant to migrate over time and be drawn in a direction into the heart chamber. Such movement can cause the implant to be moved out of axial alignment with the coronary vessel leading to occlusion of the implant.

25 The present invention is directed to an implant which resists forces tending to draw the implant into the heart chamber.

SUMMARY OF THE INVENTION

According to a preferred embodiment of the present invention, a transmyocardial implant is disclosed for establishing a blood flow path through a
30 myocardium wall between a heart chamber and a lumen of a coronary vessel residing at an exterior of said wall. The implant includes a hollow conduit having a vessel portion and a myocardial portion. The vessel portion is sized to be received within the lumen. The myocardial portion is sized to extend from the vessel through

the myocardium and into the chamber. The conduit has an open first end and an open second end on respective ones of the vessel and myocardial portions to define a blood flow pathway within an interior of the conduit between the first and second end. At least the myocardial portion of the conduit is formed of a conduit material sufficiently rigid to resist deformation and closure of the pathway in response to contraction of the myocardium. An anchor is secured to the conduit and positioned to overlie and be secured to an epicardial surface of the myocardium when the vessel portion of the conduit is secured within the lumen.

BRIEF DESCRIPTION OF THE DRAWINGS

- Fig. 1 is a side elevation, schematic view of an implant without cuff in a heart wall and illustrating tilting following implant;
- Fig. 2 is a side elevation view of an implant with an epicardial cuff;
- Fig. 3 is a top plan view of an implant of Fig. 2 with a first embodiment of an anchor;
- Fig. 4 is a side elevation view of the implant and anchor of Fig. 3;
- Fig. 5 is a distal end elevation view of the implant and anchor of Fig. 3;
- Fig. 6 is a top plan view of an implant of Fig. 2 with a second embodiment of an anchor;
- Fig. 7 is a side elevation view of the implant and anchor of Fig. 6;
- Fig. 8 is a distal end elevation view of the implant and anchor of Fig. 6;
- Fig. 9 is a top plan view of an implant of Fig. 2 with a third embodiment of an anchor;
- Fig. 10 is a side elevation view of the implant and anchor of Fig. 9;
- Fig. 11 is a distal end elevation view of the implant and anchor of Fig. 9; and
- Fig. 12 is a side elevation, cross-sectional view of an implant of Fig. 2 with a fourth embodiment of an anchor.

DESCRIPTION OF THE PREFERRED EMBODIMENT

- With initial reference to Fig. 1, an implant such as that described in U.S. Pat. Nos. 5,755,682; 5,944,019 and 5,984,956 (all incorporated herein by reference) is shown. In at least one embodiment, the implant includes a conduit in the form of an L-shaped tube. Such a conduit 10 is shown in Fig. 1.

The material of the conduit 10 is preferably a rigid material in order to withstand contraction forces of the myocardium. By way of non-limiting example, where the conduit is to be placed in a coronary vessel having an internal diameter not less than 2.5 mm, the tube will have an outside diameter of about 2.5 millimeters and an internal diameter of about 1.5 millimeters to provide a wall thickness of about .5 millimeters.

The conduit 10 has a vessel portion 12 sized to be received within the lumen of a coronary vessel such as the lumen of a coronary artery (not shown in Fig. 1 but shown in U.S. Pat. No. 5,984,956) at an upper or epicardial surface 105. The conduit 10 has a myocardial portion 14 extending at a right angle to the axis of vessel portion 12. The myocardial portion 14 is sized to extend from the coronary artery directly through the myocardium 104 and protrude into the left ventricle 106 of a patient's heart.

The tube 10 is preferably formed of titanium or other smooth biocompatible material in order to resist tissue growth on the surfaces of the conduit 10. Titanium is a presently preferred material due its long-term use in the cardiovascular industry. Further, titanium is sufficiently rigid to withstand deformation forces caused by contraction of the myocardium 104 to avoid deformation of the tube 10 so that the tube 10 remains open during both diastole and systole.

Since the titanium is resistant to thrombus formation, the titanium of the tube 10 does not fix the device within the myocardium of the patient. Therefore, as taught in U.S. Pat. No. 5,984,956, a completed implant can include a tissue growth-inducing material secured to an exterior surface of the conduit 10. Not shown in Fig. 1 but illustrated in U.S. Pat. No. 5,984,956 as a polyester fabric cuff, the tissue-growth-inducing material has interstitial spaces into which tissue of the myocardium may grow.

Fig. 1 illustrates undesirable movement of the implant 10 after surgical placement. The mechanics of the healing process and forces exerted on the device such as myocardial contraction urge the implant 10 into the myocardium 104 toward the left ventricle 106. The implant 10 responds with the myocardial portion 14 rotating distally (as shown in phantom lines in Fig. 1).

The embodiments to be described all include a short cuff 52 preferably residing only in the upper one-half to one-third thickness of the myocardium near the epicardial surface. Fig. 2 illustrates such a cuff 52. Preferably the cuff 52 has a

length that is no greater than half a length of the myocardial portion 14. By way of example, the cuff 52 has an axial length of 4 mm (compared with a 15 mm length for cuffs sized to extend the full thickness of the myocardium). Such a shortened cuff for residence in the myocardium near the epicardial surface is conveniently referred to as an "epicardial cuff". Preferably the remainder of the myocardial portion 14 not covered by the cuff 52 is highly polished to resist tissue attachment.

Figs. 3 – 5 illustrate an embodiment where the implant 10 includes a cape 60 for resisting downward movement of the proximal side of the implant 10 and distributing the forces of such resistance over large area. In the embodiments of Figs. 3 – 5 and in the remaining embodiments to be discussed, all use modifications of an implant such as that shown in Fig. 2 with an epicardial cuff 52. Accordingly, elements of such implant 10 and cuff 52 in common with such embodiments are numbered identically throughout.

In the embodiments of Figs. 3 – 5, a polyester fabric cape 60 is attached to the implant 10 at the cuff 52 (e.g. by stitching the cape 60 to the cuff 52) and fans out in a plane perpendicular to the myocardial portion 14 and extending in the proximal direction of the implant 10 (i.e., in a direction opposite the distally extending vessel portion 12).

The collar 60 overlays a ring segment 62. The ring segment is PTFE or other rigid material (which may be covered with a polyester fabric). The outer perimeter of the cape 60 is sutured to the epicardial surface of the heart wall. In the event the implant 10 is subjected to forces urging the implant 10 into the myocardium, the cape 60 resists such a motion. The load of such resistance is distributed in an arch by the ring segment 62.

Similar to the embodiment of Figs. 3 – 5, the embodiment of Figs. 6 – 8 replaces the solid cape 60 with a restraint 60' defined by a plurality of straps 61. The straps 61 extend outwardly proximally from the implant and perpendicular to the proximal-distal axis of the implant 10. The straps 61 are polyester fabric and are sutured to the epicardial surface. The straps 61 are more resistant to bunching than the cape 60 of Figs. 3 – 5. The straps 61 are stitched to the collar 52 and overlie a ring 62' similar to ring 62 of the previous embodiment. The straps radiate outwardly and to the side.

In Figs. 9 – 11, an embodiment is shown with a stabilizing clip 70 attached to the vessel portion 12. The stabilizing clip 70 includes an arcuate, thin body 72 in

the form of a flat plate bent to conform with the arcuate bend of the implant from the myocardial portion top the vessel portion. A snap clip 74 fastens the body 72 to the implant by being press fit onto the implant 10. Two support arms 76 are attached to the body 72. The support arms 76 are positioned to be spaced apart on opposite sides of the vessel portion 12 and extend generally parallel to an upper edge of the vessel portion. The support arms 76 extend beyond the vessel portion 12. Suture pads 78 of polyester fabric are provided on the free ends of the support arms 76. In the figures, the arms 76 are symmetrical. The arms can be asymmetrical with one longer than the other to span and clear any nearby vessels.

When using the implant 10 of the embodiments of Figs. 9 – 11, the implant 10 and cuff 52 (but without attached clip 70) are placed in the heart as taught in PCT Ser. No. PCT/US99/08343. The myocardial portion 14 is placed through the myocardium and the vessel portion 12 is inserted into the coronary artery. A suture (not shown) may be placed surrounding the artery over the suture groove 13. After placement of the vessel portion 14 in the artery, the clip 70 is attached to the implant 10 by snapping the clip 74 onto the implant 10 with the pads 78 resting against the epicardial surface on opposite sides of the vessel portion 12. Sutures (not shown) may be placed surrounding the clip body 72 at snap clip 74 to prevent movement of the clip 70 on the implant 10.

The clip 70 is a brace to prevent misalignment of the vessel portion 12 and coronary vessel following implantation. The snap clip 74 permits sliding positioning of the clip 70 on the implant 10 to adjust the placement at time of surgery. This insures the surgeon may place the suture pads 78 on the epicardial surface. The surgeon sutures the pads 78 to the heart.

Fig. 12 illustrates a still further embodiment for immobilizing the implant 10. In Fig. 12, a rigid support 80 is attached to the implant 10 and extends proximally. The support 80 is shaped to approximate the shape of the vessel portion 12. A suture 82 received in a groove 84 of a flexible mounting sleeve 86 anchors the support 80 to the implant 10. A polyester sleeve 88 surrounds the support 80. A suture (not shown) will surround the sleeve 88 to attach the support to the epicardial surface of the heart. As the implant 10 is urged to tilt, the support 80 abuts the heart and resists such tilting.

Having disclosed the present invention in a preferred embodiment, it will be appreciated that modifications and equivalents may occur to one of ordinary skill in

the art having the benefits of the teachings of the present invention. It is intended that such modifications shall be included within the scope of the claims which are appended hereto.


WHAT IS CLAIMED:

1. A transmymocardial implant for establishing a blood flow path through a
myocardium wall between a heart chamber and a lumen of a coronary vessel
5 residing at an exterior of said wall, said implant comprising:
a hollow conduit having a vessel portion and a myocardial portion, said
vessel adapted to be placed in fluid communication with said lumen and said
myocardial portion sized to extend from said vessel through said myocardium
wall into said chamber, said conduit having open first and second ends on
10 respective ones of said vessel and myocardial portions to define a blood flow
pathway within an interior of said conduit between said first and second ends;
at least said myocardial portion of said conduit formed of a conduit material
sufficiently rigid to resist deformation and closure of said pathway in response to
contraction of said myocardium and said conduit material resistant to thrombus
15 formation; and
an anchor secured to said conduit and positioned to overlie and be secured to
an epicardial surface of said myocardium when said vessel portion of said
conduit is secured within said lumen.
- 20 2. An implant according to claim 1 further comprising a tissue growth inducing
material secured to an exterior of said myocardial portion, said tissue growth
inducing material covering at most only half of said myocardial portion.
- 25 3. An implant according to claim 1 wherein said tissue growth inducing material is
a polyester fabric.
4. An implant according to claim 1 wherein said anchor includes an anchor
material extending from said conduit opposite a direction of said vessel portion.
- 30 5. An implant according to claim 4 wherein the myocardium wall includes an
exterior epicardial surface, and wherein said anchor material is a sheet of flexible
material adapted to extend over a surface area of said epicardial surface opposite
said vessel portion.

6. An implant according to claim 5 further comprising a load distributing member positioned between said sheet of flexible material and said epicardial surface.
- 5 7. An implant according to claim 4 wherein said anchor material is a plurality of strips of flexible material extending radially from said conduit and adapted to extend over an epicardial surface of the myocardium wall at a region positioned opposite from the vessel portion.
- 10 8. An implant according to claim 7 further comprising a load-distributing member positioned between said sheet of flexible material and said epicardial surface.
- 15 9. An implant according to claim 1 wherein said anchor includes a rigid member secured to said conduit and extending therefrom opposite said vessel portion for said rigid member to overlie an epicardial surface of the myocardium wall at a location opposite said vessel portion.
- 10 10. An implant according to claim 9 wherein said rigid member is at least partially covered with a tissue growth inducing material.
- 20 11. An implant according to claim 1 wherein said anchor extends in a direction the same as said vessel portion and includes attachment locations positioned on opposite sides of said vessel portion for attachment to an epicardial surface of the myocardium wall on opposite sides of said coronary vessel.
- 25 12. An implant according to claim 11 wherein said anchor includes a rigid brace secured to said conduit and having first and second arms extending therefrom on opposite sides of said vessel portion and terminating at said attachment locations.
- 30 13. An implant according to claim 12 wherein said brace is selectively positionable on said conduit.
14. An implant according to claim 1, wherein the anchor includes at least a portion that extends transversely outwardly from the myocardial portion.


15. An implant according to claim 1, wherein the anchor includes at least a portion that extends outwardly from the myocardial portion in a direction opposite from the vessel portion.
- 5
16. An implant according to claim 1, wherein the vessel portion is sized to be received within the vessel.
17. An implant according to claim 1, wherein the anchor includes a sheet of flexible
- 10 material connected to the conduit at a location adjacent the vessel portion.
18. An implant according to claim 1, wherein the anchor includes a rigid arm connected to the conduit at a location adjacent the vessel portion.

FIG. 1



2/6

FIG. 2






FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8

FIG. 9




FIG. 10




FIG. 11





FIG. 12



(19) World Intellectual Property Organization
International Bureau




(43) International Publication Date
18 April 2002 (18.04.2002)

(10) International Publication Number
PCT
WO 02/030326 A3

- (51) International Patent Classification⁷: **A61F 2/02, 2/06**
- (21) International Application Number: **PCT/US01/31729**
- (22) International Filing Date: **10 October 2001 (10.10.2001)**
- (25) Filing Language: **English**
- (26) Publication Language: **English**
- (30) Priority Data:
09/686,251 11 October 2000 (11.10.2000) US
60/304,165 11 October 2000 (11.10.2000) US
- (71) Applicant: **HEARTSTENT CORPORATION [US/US];**
7145 Boone Ave. N. Suite 150, Brooklyn Park, MN 55428 (US).
- (72) Inventors: **VANNEY, Guy, P.;** 10927 Buchanan Street, Blaine, MN 55434 (US). **ENO, Robert, A.;** 2535 Medicine Ridge Road, Plymouth, MN 55441 (US). **GROTH, Dale, M.;** 3224 Colorado Avenue South, St. Louis Park, MN 55416 (US).
- (74) Agent: **BRUESS, Steven, C.;** Merchant & Gould P.C., P.O. Box 2903, Minneapolis, MN 55402-0903 (US).
- (81) Designated States (*national*): AE, AG, AL, AM, AT (utility model), AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ (utility model), DE (utility model), DK (utility model), DM, DZ, EC, EE (utility model), ES, FI (utility model), GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PH, PL, PT, RO, RU, SD, SE, SG, SI, SK (utility model), SL, TJ, TM, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZW.
- (84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- Published:**
— *with international search report*
- (88) Date of publication of the international search report:
6 September 2002
- For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

(54) Title: **TRANSMYOCARDIAL IMPLANT WITH ANCHOR ELEMENT**



(57) Abstract: A transmymocardial implant for establishing a blood flow path through a myocardium between a heart chamber and a lumen of a coronary vessel residing at an exterior of said wall includes a hollow conduit having a vessel portion and a myocardial portion. The vessel portion is sized to be received within the lumen. The said myocardial portion is sized to extend from the vessel through the myocardium and into the chamber. The conduit has an open first end and an open second end on respective ones of the vessel and myocardial portions to define a blood flow pathway within an interior of the conduit between the first and second end. At least the myocardial portion of the conduit is formed of a conduit material sufficiently rigid to resist deformation and closure of the pathway in response to contraction of the myocardium. The conduit material is resistant to thrombus formation. An anchor is secured to the conduit and positioned to overlie and be secured to an epicardial surface of the myocardium when the vessel portion of the conduit is secured within the lumen.



WO 02/030326 A3

INTERNATIONAL SEARCH REPORT

International Application No

PCT/US 01/31729

A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 A61F2/02 A61F2/06

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 A61F A61B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the International search (name of data base and, where practical, search terms used)

EPO-Internal

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	WO 00 21463 A (VENTRICA INC) 20 April 2000 (2000-04-20) figures 18-21 page 7, line 32 -page 8, line 11	1
A	FR 1 514 319 A (ZACOUTO FRED) 23 February 1968 (1968-02-23) the whole document	1
A	US 5 824 071 A (SHMULEWITZ ASCHER ET AL) 20 October 1998 (1998-10-20) column 9, line 51 -column 10, line 22 figure 9	1
	-/--	

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents:

A document defining the general state of the art which is not considered to be of particular relevance

E earlier document but published on or after the international filing date

L document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

O document referring to an oral disclosure, use, exhibition or other means

P document published prior to the international filing date but later than the priority date claimed

T later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

X document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

Y document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

& document member of the same patent family

Date of the actual completion of the international search

4 June 2002

Date of mailing of the international search report

18/06/2002

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3018

Authorized officer

Mary, C

INTERNATIONAL SEARCH REPORT

International Application No
PCT/US 01/31729

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT		
Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
P,A	WO 01 17440 A (VENTRICA INC) 15 March 2001 (2001-03-15) figures 1-20 page 6, line 1 -page 9, line 20 page 11, line 12 - line 21 ---	1
P,A	WO 01 10348 A (EVANS STEPHEN ;GUILLES MARVIN (US); MLESKY GERALD (US); PERCARDIA I) 15 February 2001 (2001-02-15) page 6, line 17 -page 7, line 15 page 12, line 20 -page 13, line 2 ---	1
P,A	US 2001/025643 A1 (FOLEY MARK) 4 October 2001 (2001-10-04) figures 20-22,32-35 paragraph '0131! - paragraph '0142! paragraph '0149! - paragraph '0150! -----	1

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/US 01/31729

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
WO 0021463	A	20-04-2000	AU 6506799 A EP 1121067 A1 WO 0021463 A1	01-05-2000 08-08-2001 20-04-2000
FR 1514319	A	23-02-1968	NONE	
US 5824071	A	20-10-1998	US 5655548 A US 6186972 B1 AU 4352497 A EP 1011523 A1 JP 2001503291 T WO 9810714 A1	12-08-1997 13-02-2001 02-04-1998 28-06-2000 13-03-2001 19-03-1998
WO 0117440	A	15-03-2001	US 2001041902 A1 AU 7369800 A WO 0117440 A1	15-11-2001 10-04-2001 15-03-2001
WO 0110348	A	15-02-2001	AU 6140299 A AU 6508300 A EP 1204384 A1 EP 1112041 A1 WO 0110348 A1 WO 0015147 A1 US 2002058897 A1	03-04-2000 05-03-2001 15-05-2002 04-07-2001 15-02-2001 23-03-2000 16-05-2002
US 2001025643	A1	04-10-2001	AU 2674699 A CA 2320956 A1 EP 1054641 A1 JP 2002502663 T WO 9940868 A1 US 2001041902 A1	30-08-1999 19-08-1999 29-11-2000 29-01-2002 19-08-1999 15-11-2001

CORRECTED VERSION

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
18 April 2002 (18.04.2002)

PCT

(10) International Publication Number
WO 02/030326 A3

(51) International Patent Classification⁷: A61F 2/02, 2/06

(21) International Application Number: PCT/US01/31729

(22) International Filing Date: 10 October 2001 (10.10.2001)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
09/686,251 11 October 2000 (11.10.2000) US
60/304,165 11 October 2000 (11.10.2000) US

(71) Applicant: HEARTSTENT CORPORATION [US/US];
7145 Boone Ave. N. Suite 150, Brooklyn Park, MN 55428
(US).

(72) Inventors: VANNEY, Guy, P.; 10927 Buchanan Street,
Blaine, MN 55434 (US). ENO, Robert, A.; 2535 Medicine
Ridge Road, Plymouth, MN 55441 (US). GROTH, Dale,
M.; 3224 Colorado Avenue South, St. Louis Park, MN
55416 (US).

(74) Agent: BRUESS, Steven, C.; Merchant & Gould P.C.,
P.O. Box 2903, Minneapolis, MN 55402-0903 (US).

(81) Designated States (*national*): AE, AG, AL, AM, AT (utility model), AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ (utility model), CZ, DE (utility model), DE, DK (utility model), DK, DM, DZ, EC, EE (utility model), EE, ES, FI (utility model), FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PH, PL, PT, RO, RU, SD, SE, SG, SI, SK (utility model), SK, SL, TJ, TM, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZW.

(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).


Published:
— with international search report

(88) Date of publication of the international search report:
6 September 2002

(48) Date of publication of this corrected version:
13 November 2003

[Continued on next page]

(54) Title: TRANSMYOCARDIAL IMPLANT WITH ANCHOR ELEMENT



(57) Abstract: A transmyocardial implant for establishing a blood flow path through a myocardium between a heart chamber and a lumen of a coronary vessel residing at an exterior of said wall includes a hollow conduit having a vessel portion and a myocardial portion. The vessel portion is sized to be received within the lumen. The said myocardial portion is sized to extend from the vessel through the myocardium and into the chamber. The conduit has an open first end and an open second end on respective ones of the vessel and myocardial portions to define a blood flow pathway within an interior of the conduit between the first and second end. At least the myocardial portion of the conduit is formed of a conduit material sufficiently rigid to resist deformation and closure of the pathway in response to contraction of the myocardium. The conduit material is resistant to thrombus formation. An anchor is secured to the conduit and positioned to overlie and be secured to an epicardial surface of the myocardium when the vessel portion of the conduit is secured within the lumen.



WO 02/030326 A3



(15) **Information about Correction:**
see PCT Gazette No. 46/2003 of 13 November 2003, Sec-
tion II

*For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.*